

Page 1/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- · Product identifier
 - · Trade name: Gluma Solid Bond P
 - · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Dental bonding material
- · Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer Australia Pty Ltd 11 - 21 Underwood Rd HOMEBUSH NSW 2140

Tel: +61 (0) 2 9764 5222 Australia

- · Informing department: see above
- Emergency telephone number:

Poison Information Number: Australia 13 11 26 & New Zealand 0800 764 766

2 Hazard(s) Identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
 - GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms





GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

2-hydroxyethyl methacrylate

maleic-acid-mono-2-methacryloyl-oxyethylester maleic acid

· Hazard statements

Flammable liquid and vapour.

Causes skin İrritation.

Causes serious eye irritation. May cause an allergic skin reaction.

· Précautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



Page 2/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

(Contd. of page 1)

Specific treatment (see on this label).

- · Other hazards -
 - · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
 - · Description: Product based on methacrylates

· Dangerous com	ponents:	
CAS: 868-77-9	2-hydroxyethyl methacrylate	25-50%
EINECS: 212-782-2	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
CAS: 64-17-5	ethanol	10-25%
EINECS: 200-578-6	Flam. Liq. 2, H225	
	Poly(methacrylic-oligo-acrylic acid)	0-5%
	Eye Irrit. 2A, H319	
CAS: 109-16-0	triethylen glycol dimethacrylate	0-5%
EINECS: 203-652-6		
CAS: 51978-15-5	maleic-acid-mono-2-methacryloyl-oxyethylester	0-5%
EINECS: 257-569-5	Acute Tox. 3, H311; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 110-16-7	maleic acid	0-5%
EINEUS: 203-742-5	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
	ZA, NJ 19, JKIII JEIIS. 1, NJ 17, J 101 JE 3, NJ35	

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
 - · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Instantly rinse with water.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

- Information for doctor
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
 - Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

(Contd. on page 3)

- AÚS



Page 3/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

(Contd. of page 2)

· Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
 - Protective equipment: No special measures required.
- Additional information -

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues). Ensure adequate ventilation.

Reference to other sections

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

7 Handling and Storage

- · Handling
 - · Precautions for safe handling Keep containers tightly sealed.
 - Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - Storage
 - · Requirements to be met by storerooms and containers: Store in cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Store cool (not above 25 $\,^\circ$ C).

Store in cool, dry conditions in well sealed containers.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

Components with critical values that require monitoring at the workplace:
64-17-5 ethanol

NES (Australia)	1880 mg/m³, 1000 ppm
PFL (USA)	1900 ma/m ³ 1000 ppm
REL (USA)	1900 mg/m³, 1000 ppm
TLV (USA)	1880 mg/m³, 1000 ppm

(Contd. on page 4)



Page 4/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

			(Contd. of page
	DNELs		
64-17-5 et	hanol		
Oral	ge.pop., l.:	te, syst.	87 mg/Kg (nd)
Dermal	worker pro	ofess., l.te., syst.	343 mg/Kg/d (nd)
ge.p	ge.pop., a	cu., local	950 mg/Kg/d (nd)
	ge.pop., l.:	te, syst.	206 mg/Kg/d (nd)
-	worker pro	ofess., acute, local	1900 mg/m3 (nd)
	worker pro	ofess., l.te., syst.	1900 mg/m3 (nd)
	ge.pop., a	cu., local	950 mg/m3 (nd)
	ge.pop., l.:	te, syst.	114 mg/m3 (nd)
109-16-0 t	riethylen	glycol dimethacry	late
Dermal	worker industr., l.te., syst.		13.9 mg/Kg/d (nd)
Inhalative	worker industr., l.te., syst.		48.5 mg/m3 (nd)
.	PNECs		
64-17-5 et	hanol		
freshwater	•	0.96 mg/l (nd)	
marine wa	ter	0.79 mg/l (nd)	
STP		580 mg/l (nd)	
sedim., du	, fre.wat.	3.6 mg/Kg (nd)	
soil,dw		0.63 mg/Kg (nd)	
109-16-0 t	riethylen g	glycol dimethacry	rlate
marine wa	ter	0.0164 mg/l (nd)	
sedim., dw	, fre.wat.	1.85 mg/Kg (nd)	
		0.185 mg/Kg (nd)	
soil,dw	•	0.274 mg/Kg (nd)	

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

Personal protective equipment

General protective and hygienic measures

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Use breathing protection in case of insufficient ventilation.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

(Contd. on page 5)



Page 5/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

Eye protection:

Protective goggles are recommended.
Tightly sealed safety glasses.
Body protection: Light weight protective clothing

9 Physical and Chemical Properties

Information on basic physical and che General Information	mical properties
· Appearance:	
Form:	Fluid
· Colour:	Yellowish
· Smell:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Not determined
Initial boiling point and boiling ra	ange: 55 ℃
· Flash point:	35 ℃
· Inflammability (solid, gaseous)	Not applicable.
Ignition temperature:	<i>425.0</i> ℃
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
· Critical values for explosion:	
Lower:	3.5 Vol %
· Upper:	15.0 Vol %
· Steam pressure at 20 ℃:	57 hPa
· Density at 20 ℃	1.000 g/cm³
· Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible

(Contd. on page 6)



Page 6/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

		(Contd. of page 5)
· Partition coefficient: n-octa	nol/water: Not determined.	
Viscosity: dynamic at 20 ℃: kinematic:	1 mPas Not determined.	
Solvent content: Water:	31.9 %	
Solids content: Other information	1.3 % No further relevant information available.	

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Chemical stability
 Conditions to be avoided: No decomposition if used and stored according to specifications.
 Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: None

11 Toxicological Information

- · Information on toxicological effects
 - Acute toxicity

710010		
· LD /	LC50 valu	es that are relevant for classification:
868-77-9	2-hydroxy	ethyl methacrylate
Oral	LD50	5564 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (can)
64-17-5 et	thanol	
Oral	LD50	6200 mg/kg (rat)
Inhalative	LC50/4 h	95.6 mg/l (rat)
Poly(meti	hacrylic-o	ligo-acrylic acid)
Oral	LD50	>5000 mg/kg (rat)
109-16-0	triethylen	glycol dimethacrylate
Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (mouse)
51978-15-	5 maleic-a	acid-mono-2-methacryloyl-oxyethylester
Oral	LD50	1068 mg/kg (rat)
110-16-7	maleic aci	d
Oral	LD50	708 mg/kg (rat)
Dermal	LD50	1560 mg/kg (rab)
. Prii	narv irrita	nt effect

- - · Skin corrosion/irritation Irritant for skin and mucous membranes.
 - · Serious eye damage/irritation Irritant effect.
- · Respiratory or skin sensitisation Sensitization possible by skin contact.

(Contd. on page 7)



Page 7/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

(Contd. of page 6)

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
 - · Aquatic toxicity:

868-77-9 2-hydroxyethyl methacrylate

LC50/96h | 227 mg/l (fish)

109-16-0 triethylen glycol dimethacrylate

EC50/72h > 100 mg/l (algae)

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.
 - · Recommended cleaning agent: Water, if necessary with cleaning agent.

4 Transport information	
· UN-Number · ADG, IMDG, IATA	1170
· UN proper shipping name · ADG	1170 ETHANOL SOLUTION (ETHYL ALCOHO
· IMDG	SOLUTION) ETHANOL SOLUTION (ETHYL ALCOHO
· IATA	SOLUTION) ETHANOL, solution

(Contd. on page 8)



Page 8/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

(Contd. of page 7)

· Transport hazard class(es)

· ADG, IMDG, IATA



3 Flammable liquids. · Class

· Label

· Packing group ADĞ, ĬMDĠ, IATA III

Environmental hazards: · Marine pollutant:

No · Special precautions for user Warning: Flammable liquids.

· Kemler Number: 30 · EMS Number: F-E,S-D

Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

UN1170, ETHANOL SOLUTION (ETHYL ALCOHOL · UN "Model Regulation":

SOLUTION), 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling: 2-hydroxyethyl methacrylate

maleic-acid-mono-2-methacryloyl-oxyethylester maleic acid

Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 9)



Page 9/9

Safety Data Sheet according to WHS Regulations

Printing date 05.07.2018 Version number 3 Revision: 05.07.2018

Trade name: Gluma Solid Bond P

(Contd. of page 8)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowe'd.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PRT: Persistent Rinaccumulative and Toxic

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skip Irst 2: Skip personal (Irst table)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

AUS