



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

1 Identification

· **Product identifier**

· **Trade name:** Signum ceramic bond I

· **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehkna@kulzer-dental.com

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

propan-2-ol

acetone

· **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

CDN



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 1)

Store locked up.

Hazard description:

Canadian Hazard Symbols

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects



Classification system

NFPA ratings for USA (scale 0-4)



Health = 1
Fire = 3
Reactivity = 0

HMIS-Ratings (Scale 0-4)



Health = 1
Fire = 3
Reactivity = 0

Other hazards -

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: -

Dangerous components:

67-63-0	propan-2-ol Flammable Liquids - Category 2, H225; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	75-90% w/w
67-64-1	acetone Flammable Liquids - Category 2, H225; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	5-10% w/w

Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

Description of first aid measures

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact Generally the product does not irritate the skin.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

(Contd. on page 3)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 2)

- **Information for doctor**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
 - **Protective equipment:** No special measures required.
- **Additional information -**

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).
Ensure adequate ventilation.
- **Reference to other sections**
No dangerous substances are released.
See Section 8 for information on personal protection equipment.
-

7 Handling and storage

- **Handling**
 - **Precautions for safe handling** Keep receptacles tightly sealed.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

· **Specific end use(s)** No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol

EL Short-term value: 400 ppm
Long-term value: 200 ppm

EV Short-term value: 400 ppm
Long-term value: 200 ppm

67-64-1 acetone

EL Short-term value: 500 ppm
Long-term value: 250 ppm

EV Short-term value: 750 ppm
Long-term value: 500 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

(Contd. on page 5)

CDN



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 4)

Nitrile rubber, NBR

- **Eye protection:**
Protective goggles are recommended.
Tightly sealed goggles.
- **Body protection:** Light weight protective clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Fluid

· **Color:** Colorless

· **Odor:** Alcohol-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/Melting range:** undetermined

· **Boiling point/Boiling range:** 55 °C (131 °F)

· **Flash point:** 5 °C (41 °F)

· **Flammability (solid, gaseous)** Not applicable.

· **Ignition temperature:** >400 °C (>752 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:** 2.0 Vol %

· **Upper:** 12.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 48 hPa (36 mm Hg)

· **Density at 20 °C (68 °F):** 0.800 g/cm³ (6.676 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Fully miscible

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **dynamic:** Not determined.

· **kinematic:** Not determined.

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 5)

- **Solvent content:**
- **Water:** 4.0 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** none

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

67-63-0 propan-2-ol

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

67-63-0	propan-2-ol	3
80-62-6	methyl methacrylate	3
102-71-6	2,2',2"-nitrioltriethanol	3
7647-01-0	hydrogen chloride	3
	Butyl-hydroxy-toluol	3

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

67-63-0 propan-2-ol

EC50/72h >1000 mg/l (algae)
SDB Fa. Merck v. 16.07.2010

EC50/48h 13299 mg/l (daphnia)
SDB Fa. Merck v. 16.07.2010

LC50/96h 1400 mg/l (fish)
SDB Fa. Merck v. 16.07.2010

67-64-1 acetone

EC50/48h 6100 mg/l (daphnia)

LC50/96h 5540 mg/l (fish)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

CDN

(Contd. on page 8)



Safety Data Sheet
acc. to OSHA HCS




Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 7)

14 Transport information

· UN-Number · DOT, TDG, IMDG, IATA	UN1993
· UN proper shipping name · TDG · IMDG, IATA	1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE) FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)
· Transport hazard class(es) · DOT  · Class · Label · TDG (Transport dangerous goods):  · Class · Label	3 Flammable liquids 3 3 (F1) Flammable liquids 3
· IMDG, IATA  · Class · Label	3 Flammable liquids 3
· Packing group · DOT, TDG, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids 33 F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 8)

- **Transport/Additional information:** -
- **UN "Model Regulation":** UN1993, Flammable liquids, n.o.s., special provision 640D (Isopropanol (Isopropyl alcohol), Acetone), 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **SARA Section 355 (extremely hazardous substances)**

7647-01-0 | hydrogen chloride

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
 - propan-2-ol
 - acetone
- **Hazard statements**
 - Highly flammable liquid and vapour.
 - Causes serious eye irritation.
 - May cause drowsiness or dizziness.
- **Precautionary statements**
 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - Use explosion-proof [electrical/ventilating/lighting] equipment.
 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - Store locked up.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 10)

CDN



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/03/2017

Reviewed on 06/03/2017

Trade name: Signum ceramic bond I

(Contd. of page 9)

- **Date of preparation / last revision** 06/03/2017 / 2
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - WHMIS: Workplace Hazardous Materials Information System (Canada)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
- *** Data compared to the previous version altered.**

CDN