



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

1 Identification

· **Product identifier**

· **Trade name: Palaferm insulation**

· **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehka@kulzer-dental.com

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves / eye protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

· **Classification system**

· **NFPA ratings for USA (scale 0-4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-Ratings (Scale 0-4)**



Health = 2

Fire = 3

Reactivity = 0

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 2)



**Safety Data Sheet
acc. to OSHA HCS**

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

· **vPvB:** Not applicable.

(Contd. of page 1)

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** -

· **Dangerous components:**

64-17-5	ethanol	Flam. Liq. 2, H225	≥50-≤75%
10035-04-8	calcium chloride, dihydrate	Eye Irrit. 2A, H319	≥10-≤25%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation** Supply fresh air; consult doctor in case of complaints.

· **After skin contact** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

· **Additional information** -

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Avoid contact with eyes and skin.

· **Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).

· **Reference to other sections**

No dangerous substances are released.

See Section 8 for information on personal protection equipment.

-

(Contd. on page 3)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 2)

· Protective Action Criteria for Chemicals

· PAC-1:		
64-17-5	ethanol	1,800 ppm
10035-04-8	calcium chloride, dihydrate	16 mg/m ³
78-93-3	butanone	200 ppm
· PAC-2:		
64-17-5	ethanol	3300* ppm
10035-04-8	calcium chloride, dihydrate	170 mg/m ³
78-93-3	butanone	2700* ppm
· PAC-3:		
64-17-5	ethanol	15000* ppm
10035-04-8	calcium chloride, dihydrate	1,100 mg/m ³
78-93-3	butanone	4000* ppm

7 Handling and storage

· Handling

- **Precautions for safe handling** Keep receptacles tightly sealed.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment

- **General protective and hygienic measures**
Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not necessary if room is well-ventilated.

(Contd. on page 4)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 3)

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

· **Eye protection:** Tightly sealed goggles.

· **Body protection:** Light weight protective clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Liquid

· **Color:**

Colorless

· **Odor:**

Alcohol-like

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

undetermined

· **Boiling point/Boiling range:**

78 °C (172.4 °F)

· **Flash point:**

14 °C (57.2 °F)

· **Flammability (solid, gaseous)**

Not applicable.

· **Ignition temperature:**

400 °C (752 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

3.5 Vol %

· **Upper:**

15.0 Vol %

· **Vapor pressure at 20 °C (68 °F):**

57 hPa (42.8 mm Hg)

· **Density at 20 °C (68 °F):**

0.930 g/cm³ (7.76085 lbs/gal)

· **Relative density**

Not determined.

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 4)

· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· dynamic:	Not determined.
· kinematic:	Not determined.
· Solvent content:	
· VOC USA	1486.9 g/l / 12.41 lb/gl
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** none

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
64-17-5 ethanol		
Oral	LD50	6,200 mg/kg (rat)
Inhalative	LC50/4 h	95.6 mg/l (rat)
10035-04-8 calcium chloride, dihydrate		
Oral	LD50	2,301 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)	
64-17-5 ethanol	1

· NTP (National Toxicology Program)	
None of the ingredients is listed.	

· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

US
(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 5)

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

10035-04-8 calcium chloride, dihydrate

EC50/48h 144 mg/l (daphnia)

LC50/96h 10.65 mg/l (fish)

IC 50/ 72h 3.13 mg/l (algae)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN1170

· **UN proper shipping name**

· **DOT**

Ethanol solution

· **ADR**

1170 ETHANOL (ETHYL ALCOHOL) solution

· **IMDG**

ETHANOL (ETHYL ALCOHOL) solution

· **IATA**

ETHANOL solution

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 6)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
· **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler**

code): 33

· **EMS Number:** 3-06

· **Stowage Category** A

· **Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code Not applicable.

· **Transport/Additional information:** -

· **ADR**

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)** 1L

(Contd. on page 8)



**Safety Data Sheet
acc. to OSHA HCS**

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 7)

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1170 ETHANOL (ETHYL ALCOHOL) SOLUTION, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **SARA Section 355 (extremely hazardous substances)**

None of the ingredients is listed.

· **SARA Section 313 (specific toxic chemical listings)**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Prop 65 - Chemicals known to cause cancer**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 ethanol

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

78-93-3 butanone

I

· **TLV (Threshold Limit Value established by ACGIH)**

64-17-5 ethanol

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

· **Date of preparation / last revision** 11/09/2020 / 2

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/09/2020

Reviewed on 11/09/2020

Trade name: Palaferm insulation

(Contd. of page 8)

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
* **Data compared to the previous version altered.**

US