

Page 1/11

Safety data sheet according to 1907/2006/EC. Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking · 1.1 Product identifier • Trade name: Signum zirconia bond I 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Zirconia-Resin Bonding System · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Kulzer GmbH Leipziger Straße 2, 63450 Hanau (Germany) Tel.: +49 (0)800 4372522 · Informing department: E-Mail: msds@kulzer-dental.com • 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463 SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 2 H225 Highly flammable liquid and vapour. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: acetone · Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210 No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves / eye protection. P337+P313 If eye irritation persists: Get medical advice/attention. Additional information: Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9. · 2.3 Other hazards -(Contd. on page 2)



Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

(Contd. of page 1)

Trade name: Signum zirconia bond I

Results of PBT and vPvB assessment

CECTION 2: Company a sitis m/information on insure dia

• **PBT:** Not applicable.

• vPvB: Not applicable.

3.2 Mixtures [•] Description: -		
 Dangerous components: 		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	>90%
CAS: 85590-00-7 EC number: 874-929-2	10-(Phosphonooxy)decyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0-5%
CAS: 64-19-7 EINECS: 200-580-7 Index number: 607-002-00-6 Reg.nr.: 01-2119475328-30-XXXX	acetic acid Flam. Liq. 3, H226 Skin Corr. 1A, H314; Eye Dam. 1, H318 (Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90 % Skin Corr. 1B; H314: 25 % ≤ C < 90 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %	≥1-< 3%

SECTION 4: First aid measures

- [•] 4.1 Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of symptoms.
 - · After skin contact
 - Instantly wash with water and soap and rinse thoroughly.
 - If skin irritation continues, consult a doctor.
 - After eye contact Rinse opened eye for several minutes under running water. Then consult doctor. After swallowing

Rinse out mouth and then drink plenty of water.

- In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. For safety reasons unsuitable extinguishing agents Water with a full water jet. 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures. Formation of toxic gases is possible during heating or in case of fire. 5.3 Advice for firefighters Protective equipment: Wear self-contained breathing apparatus.
 - Wear full protective suit. • Additional information -

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with eyes and skin. Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues). Ensure adequate ventilation.

Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

- See Section 13 for information on disposal.
- See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

[.] 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

- Storage
 - · Requirements to be met by storerooms and containers: Store in cool location.
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:
 - Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 3)

8.1 Contro	ol parameters			
	<u>.</u>	tical valu	es that require	monitoring at the workplace:
67-64-1 a			· · ·	• ·
		n value: 1210 mg/m³, 500 ppm		
IOELV (Eu	uropean Union)	Long-terr	n value: 1210 n	ng/m³, 500 ppm
64-19-7 a	cetic acid			
OEL (Ireland) Short-tern Long-tern IOEL V		n value: 50 mg/m³, 20 ppm n value: 25 mg/m³, 10 ppm		
IOELV (Eu	ıropean Union)	Short-teri Long-terr	m value: 50 mg/m³, 20 ppm n value: 25 mg/m³, 10 ppm	
· DN	ELs			
67-64-1 a	cetone			
Oral	general popula	tion, long	term, systemic	62 mg/Kg (not defined)
Dermal	worker industri	al, long te	rm, systemic	186 mg/Kg/d (not defined)
	general popula	tion, long	term, systemic	62 mg/Kg/d (not defined)
Inhalative	worker industri	al, long te	rm, systemic	1,210 mg/m3 (not defined)
	worker industri	al, long te	rm, local	2,420 mg/m3 (not defined)
	general popula	tion, long	term, systemic	200 mg/m3 (not defined)
· PNI	ECs			
67-64-1 a	cetone			
freshwater	r		10.6 mg/l (not defined)	
marine wa	ter		1.06 mg/l (rabbit)	
sewage treatment plant		19.5 mg/l (not defined)		
-	dry weight, fres	hwater	30.4 mg/Kg (not defined)	
sediment, dry weight, marine water		, ,		
soil, dry weight		0.112 mg/Kg (not defined)		
	-	ation: The		valid during the compilation were used as basis.
Appro Individ Ger Avo Kee Inst Wa Avo Bre	lual protection neral protective id contact with to p away from foo antly remove ar sh hands during id contact with to athing equipm	measure e and hyg the eyes. odstuffs, b ny soiled a breaks a the eyes a ent:	s, such as per- ienic measure everages and f nd impregnated nd at the end of nd skin.	ood. I garments. ^f the work.
Not	neccessary wi	th efficier	nt local exhaus	t. If exposition to vapours is possible, use breathin
	ective mask (filt	(a. a. A.)		



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

Trade name: Signum zirconia bond I

· Hand protection

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

recommended • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- Butyl rubber, BR
- Nitrile rubber, NBR

· Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

9.1 Information on basic physical and chen	nical properties
· General Information	
· Physical state	Fluid
· Colour:	Colourless
· Smell:	Acetone-like
· Odour threshold:	Not determined.
 Melting point/freezing point: 	Not determined
· Boiling point or initial boiling point a	nd
boiling range	55 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	2.6 Vol %
· Upper:	13.0 Vol %
Flash point:	-19 °C
Auto-ignition temperature:	465 °C
Decomposition temperature:	Not determined.
SADT	
• pH	Mixture is non-soluble (in water).
· Viscosity:	
Kinematic viscosity	Not determined.
Kinematic viscosity	Not determined.
· dynamic:	Not determined.

(Contd. on page 6)



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

Trade name: Signum zirconia bond I

	(Contd. of page
· Solubility	
· Water:	Not miscible or difficult to mix
 Partition coefficient n-octanol/water (log 	
value)	Not determined.
Steam pressure at 20 °C:	247 hPa
· Vapour pressure:	
Density and/or relative density	
· Density	Not determined
Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information Not	further relevant information available.
· Appearance:	
Form:	Fluid
 Important information on protection of health 	
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
 Explosive properties: 	Product is not explosive. However, formation of
	explosive air/vapour mixtures is possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard	
classes	
Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
[•] Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
[•] Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
• Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
 Conditions to be avoided: No decomposition if used and stored according to specifications.
 10.3 Possibility of hazardous reactions No dangerous reactions known

(Contd. on page 7)

IE



Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

(Contd. of page 6)

Trade name: Signum zirconia bond I

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: None

Additional information: -

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

67-64-1 acetone				
Oral	LD50	5,800 mg/kg (rat)		
Dermal	LD50 LD50	5,800 mg/kg (rat) >15,800 mg/kg (rabbit)		

Inhalative LC50/4 h 76 mg/l (rat) 64-19-7 acetic acid

Oral LD50 3,310 mg/kg (rat)

Inhalative LC50/4 h 11.4 mg/l (rat) (OECD 403)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

- Aspiration hazard Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· 11.2 Information on other hazards

· Endocrine disrupting properties 128-37-0 2,6-di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· Aquatic	toxicity:	
67-64-1 ace	etone	
EC50/48h	8,800 mg/l (daphnia)	
LC50/96h	6,210 mg/l (fish) (OECD 203)	
64-19-7 ace	etic acid	
EC50/48h	>300.82 mg/l (daphnia) (OECD 202)	
	(C	Contd. on page



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

(Contd. of page 7)

Trade name: Signum zirconia bond I

LC50/96h >1,000 mg/l (fish) (OECD 203) ErC50 / 72 h >1,000 mg/l (algae) NOEC / 72h 1.000 mg/l (algae)

NOEC / 96h 1,000 mg/l (fish) (OECD 203)

· 12.2 Persistence and degradability

67-64-1 acetone

Biodegradation 90.9 % /28d (not defined) (OECD 301D)

64-19-7 acetic acid

Biodegradation 96 % /20d (not defined)

· 12.3 Bioaccumulative potential No further relevant information available.

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

18 01 06* chemicals consisting of or containing hazardous substances

· Uncleaned packagings:

· Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

SECTION 14: Transport information

• 14.1 UN number or ID number ADR, IMDG, IATA

14.2 UN proper shipping name ADR

· IMDG, IATA

1090 ACETONE solution ACETONE solution

UN1090

(Contd. on page 9)



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

Trade name: Signum zirconia bond I

	(Contd. of page
 14.3 Transport hazard class(es) 	
ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
*	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMĎĞ, IAŤA	11
· 14.5 Environmental hazards:	Ma
Marine pollutant:	No
14.6 Special precautions for user Kemler Number:	Warning: Flammable liquids. 33
· EMS Number:	55 F-E,S-D
· Stowage Category	E
14.7 Maritime transport in bulk according to	
instruments	Not applicable.
• Transport/Additional information:	· · · · · · · · · · · · · · · · · · ·
· ADR	1L
 Limited quantities (LQ) Excepted quantities (EQ) 	Code: E2
	Maximum net quantity per inne
	packaging: 30 ml
	Maximum net quantity per out
Trenenertesterre	packaging: 500 ml
 Transport category Tunnel restriction code 	2 D/E
· IMDG	11
 Limited quantities (LQ) Excepted quantities (EQ) 	1L Codo: E2
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inne
	packaging: 30 ml
	Maximum net quantity per oute
	packaging: 500 ml
	(Contd. on page



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

(Contd. of page 9)

Trade name: Signum zirconia bond I

· UN "Model Regulation":

UN 1090 ACETONE SOLUTION, 3, II

SECTION 15: Regulatory information · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Directive 2012/18/EU Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3 · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II None of the inaredients is listed. · REGULATION (EU) 2019/1148 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)) no information available · Annex II - REPORTABLE EXPLOSIVES PRECURSORS 67-64-1 acetone · Regulation (EC) No 273/2004 on drug precursors 67-64-1 acetone 3 \cdot Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors 67-64-1 acetone 3 • 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- Date of previous version: 03.08.2022
- Version number of previous version: 3
- Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

(Contd. on page 11)

IF



Page 11/11

IF

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2024

Version number 4 (replaces version 3)

Revision: 08.07.2024

Trade name: Signum zirconia bond I

(Contd. of page 10) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ELINCS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent DD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 1 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 * * Data compared to the previous version altered.