



**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- **1.1 Product identifier**
 - Trade name: **Signum composite flow**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

 - Application of the substance / the mixture Veneering resin
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
Kulzer GmbH
Leipziger Straße 2, 63450 Hanau (Germany) Tel.: +49 (0)800 4372522
 - **Informing department:** E-Mail: msds@kulzer-dental.com
- **1.4 Emergency telephone number:** Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - Classification according to Regulation (EC) No 1272/2008
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **2.2 Label elements**
 - Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
 - Hazard pictograms



GHS07

- Signal word Warning
- Hazard-determining components of labelling:
triethylen glycol dimethacrylate
methyl methacrylate
- Hazard statements
H317 May cause an allergic skin reaction.
- Precautionary statements
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- **2.3 Other hazards -**
 - Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.

· **Determination of endocrine-disrupting properties**

131-57-7 Oxybenzone

List II

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
 - Description: -

(Contd. on page 2)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 1)

Dangerous components:

CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21-xxxx	triethylen glycol dimethacrylate Skin Sens. 1B, H317	≥10-≤25%
CAS: 41637-38-1 EC number: 609-946-4	bisphenol a polyethylene glycol diether dimethacrylate Aquatic Chronic 4, H413	≥0-≤5%
CAS: 131-57-7 EINECS: 205-031-5	Oxybenzone Aquatic Acute 1, H400; Aquatic Chronic 2, H411	≥0.25-<1%
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Supply fresh air; consult doctor in case of symptoms.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

Additional information -

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Do not allow to enter the ground/soil.

(Contd. on page 3)



**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
Send for recovery or disposal in suitable containers.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.
-

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Wear protective equipment. Keep unprotected persons away.
 - **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and containers:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

- **Components with critical values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

OEL (Ireland)	Short-term value: 100 ppm Long-term value: 50 ppm IOELV, Sens
IOELV (European Union)	Short-term value: 100 ppm Long-term value: 50 ppm

· **DNELs**

109-16-0 triethylen glycol dimethacrylate

Oral	general population, long term, systemic	8.33 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.9 mg/Kg/d (not defined)
	general population, long term, systemic	8.33 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	48.5 mg/m ³ (not defined)
	general population, long term, systemic	14.5 mg/m ³ (not defined)

41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate

Oral	general population, long term, systemic	5 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	140 mg/Kg/d (not defined)
	general population, long term, systemic	50 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	98.7 mg/m ³ (not defined)
	general population, long term, systemic	17.4 mg/m ³ (not defined)

131-57-7 Oxybenzone

Oral	general population, long term, systemic	2 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	39 mg/Kg/d (not defined)
	general population, long term, systemic	20 mg/Kg/d (not defined)

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 3)

<i>Inhalative</i>	<i>worker industrial, long term, systemic</i>	27.7 mg/m ³ (not defined)
	<i>general population, long term, systemic</i>	6.8 mg/m ³ (not defined)
80-62-6 methyl methacrylate		
<i>Oral</i>	<i>general population, long term, systemic</i>	8.2 mg/Kg (not defined)
<i>Dermal</i>	<i>worker industrial, long term, systemic</i>	13.67 mg/Kg/d (not defined)
	<i>general population, long term, systemic</i>	8.2 mg/Kg/d (not defined)
<i>Inhalative</i>	<i>worker industrial, acute, local</i>	416 mg/m ³ (not defined)
	<i>worker industrial, long term, systemic</i>	348.4 mg/m ³ (not defined)
	<i>worker industrial, long term, local</i>	208 mg/m ³ (not defined)
	<i>general population, acute, local</i>	208 mg/m ³ (not defined)
	<i>general population, long term, systemic</i>	74.3 mg/m ³ (not defined)

· PNECs

109-16-0 triethylen glycol dimethacrylate

<i>freshwater</i>	0.016 mg/l (not defined)
<i>marine water</i>	0.002 mg/l (not defined)
<i>sewage treatment plant</i>	1.7 mg/l (not defined)
<i>sediment, dry weight, freshwater</i>	0.185 mg/Kg (not defined)
<i>sediment, dry weight, marine water</i>	0.018 mg/Kg (not defined)
<i>soil, dry weight</i>	0.027 mg/Kg (not defined)

131-57-7 Oxybenzone

<i>freshwater</i>	0.00067 mg/l (not defined)
<i>marine water</i>	0.00067 mg/l (not defined)
<i>sewage treatment plant</i>	10 mg/l (not defined)
<i>sediment, dry weight, freshwater</i>	0.066 mg/Kg (not defined)
<i>sediment, dry weight, marine water</i>	0.007 mg/Kg (not defined)
<i>soil, dry weight</i>	0.013 mg/Kg (not defined)

80-62-6 methyl methacrylate

<i>freshwater</i>	0.94 mg/l (not defined)
<i>marine water</i>	0.094 mg/l (not defined)
<i>sewage treatment plant</i>	10 mg/l (not defined)
<i>sediment, dry weight, freshwater</i>	10.2 mg/Kg (not defined)
<i>sediment, dry weight, marine water</i>	0.102 mg/Kg (not defined)
<i>soil, dry weight</i>	1.48 mg/Kg (not defined)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Wash hands during breaks and at the end of the work.

· Breathing equipment: Not necessary if room is well-ventilated.

· Hand protection

Check protective gloves prior to each use for their proper condition.
recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 4)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Butyl rubber, BR
Nitrile rubber, NBR
- **Eye/face protection** Safety glasses
- **Body protection:** Light weight protective clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

- **Physical state** Fluid
- **Colour:** Brown
White
Pink
Colourless
Odourless
- **Smell:** Odourless
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 255 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
· **Lower:** Not determined.
· **Upper:** Not determined.
- **Flash point:** >100 °C (109-16-0 triethylen glycol dimethacrylate)
Not determined.
- **Decomposition temperature:** Not determined.
- **SADT** Mixture is non-soluble (in water).
- **pH**
- **Viscosity:**
· **Kinematic viscosity** Not determined.
· **dynamic:** Not determined.
- **Solubility**
· **Water:** Not miscible or difficult to mix
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Steam pressure:** Not determined.
- **Density and/or relative density**
· **Density** Not determined
· **Relative density** Not determined.
· **Vapour density** Not determined.

· **9.2 Other information**

No further relevant information available.

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
· **Self-inflammability:** Product is not selfigniting.
· **Explosive properties:** Product is not explosive.
Not determined.

(Contd. on page 6)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 5)

- **Solvent content:**
 - **Water:** 1.3 %
 - **Solids content:** 9.6 %
- **Change in condition**
 - **Evaporation rate** Not determined.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None
 - **Additional information:** -

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

109-16-0 triethylen glycol dimethacrylate

Oral	LD50	8,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (mouse)

68611-44-9 Silane, dichlorodimethyl-, reaction products with silica

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC0/4h	0.477 mg/L (rat)

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 6)

41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

131-57-7 Oxybenzone

Oral	LD50	>12,800 mg/kg (rat) (OECD 401)
Dermal	LD50	>16,000 mg/kg (rabbit) (OECD 402)

80-62-6 methyl methacrylate

Oral	LD50	~7,900 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)
Inhalative	LC50/4 h	29.8 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

- **Aquatic toxicity:**

65997-17-3 Glaspulver

EC50/72h	>1,000 mg/l (daphnia)
LC50/96h	>1,000 mg/l (fish)
ErC50 / 72 h	>1,000 mg/l (algae)
NOEC / 72h	1,000 mg/l (algae)
	1,000 mg/l (daphnia)

109-16-0 triethylen glycol dimethacrylate

EC50/21d	51.9 mg/L (daphnia) (OECD 211)
LC50/96h	16.4 mg/l (fish) (OECD 203)
NOEC / 21d	32 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>100 mg/l (algae) (OECD 201)
NOEC / 72h	18.6 mg/l (algae) (OECD 201)
EbC50 / 72h	72.8 mg/l (algae) (OECD 201)

68611-44-9 Silane, dichlorodimethyl-, reaction products with silica

LC50/96h	>10,000 mg/l (fish) (OECD 203)
ErC50 / 72 h	>10,000 mg/l (algae) (OECD 201)
EC50 / 24h	>10,000 mg/l (daphnia) (OECD 202)

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 7)

41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate

LL50/96h	>100 mg/L (fish) (OECD 203)
EL50/48h	>100 mg/L (daphnia) (OECD 202)
EL50/72h	>100 mg/L (algae) (OECD 201)
NOEC / 21d	≥0.00224 mg/l (daphnia) (OECD 211)

131-57-7 Oxybenzone

EC50/48h	1.87 mg/l (daphnia) (OECD 202)
LC50/96h	3.8 mg/l (fish) (OECD 203)
ErC50 / 72 h	0.67 mg/l (algae) (OECD 201)
NOEC / 72h	0.18 mg/l (algae) (OECD 201)
NOEC / 96h	0.72 mg/l (fish) (OECD 203)
NOEC / 48h	1.15 mg/l (daphnia) (OECD 202)

80-62-6 methyl methacrylate

EC50/21d	49 mg/L (daphnia) (OECD 211)
EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)
NOEC / 21d	37 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)
NOEC / 72h	110 mg/l (algae) (OECD 201)
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)
EbC50 / 72h	>110 mg/l (algae) (OECD 201)
NOEC/ 35d	9.4 mg/L (fish) (OECD 210)
LC50/ 35d	33.7 mg/L (fish) (OECD 210)

12.2 Persistence and degradability

109-16-0 triethylen glycol dimethacrylate

Biodegradation	85 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)
----------------	--

41637-38-1 bisphenol a polyethylene glycol diether dimethacrylate

Biodegradation	24 % /28d (not defined) (OECD 301D)
----------------	-------------------------------------

131-57-7 Oxybenzone

Biodegradation	60-70 % /28d (not defined)
----------------	----------------------------

80-62-6 methyl methacrylate

Biodegradation	94 % /14d (not defined) (OECD 301C)
----------------	-------------------------------------

12.3 Bioaccumulative potential

131-57-7 Oxybenzone

Bioconcentration factor (BCF)	>33-<160 (fish) (OECD 305)
-------------------------------	----------------------------

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
 - **Remark:** Harmful to fish
 - **Additional ecological information:**
 - **General notes:**
Avoid transfer into the environment.

(Contd. on page 9)



**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

Harmful to aquatic organisms

(Contd. of page 8)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **European waste catalogue**

18 01 06* | chemicals consisting of or containing hazardous substances

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· ADR, ADN, IMDG, IATA

Void

· **14.2 UN proper shipping name**

· ADR, ADN, IMDG, IATA

Void

· **14.3 Transport hazard class(es)**

· ADR, ADN, IMDG, IATA

· Class

Void

· **14.4 Packing group**

· ADR, IMDG, IATA

Void

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

-

· **UN "Model Regulation":**

Void

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 10)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.11.2022

Version number 4 (replaces version 3)

Revision: 17.11.2022

Trade name: Signum composite flow

(Contd. of page 9)

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

no information available

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

no information available

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· **Date of previous version: 30.06.2022**

· **Version number of previous version: 3**

· **Abbreviations and acronyms:**

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· *** Data compared to the previous version altered.**